FIIG	**TITLE**	**INCs**	**Due Date**
A273	Gears	17	May 3, 2002

INC 26666 - GEAR, ANTIBACKLASH, BEVEL – App Key 'AA'

No change.

INC 26667 - GEAR, ANTIBACKLASH, HELICAL – App Key 'AB'

Delete the following MRCs:
CQQR (Thread Pitch In Millimeters)
CMLM (Mounting Hole Thread Quantity Per Inch)

INC 26668 - GEAR, ANTIBACKLASH, SPUR – App Key 'AC'

Delete the following MRCs:
CQQR (Thread Pitch In Millimeters)
SUPP (Supplementary Features)

INC 26669 - GEAR, ANTIBACKLASH, WORM WHEEL – App Key 'AD'

Delete MRC STDC (Surface Treatment Document And Classification)

INC 05463 - GEAR (1), BEVEL, App Key 'AE'

Delete the following MRCs:
TMQY (Furnished Items And Quantity)
CBBL (Features Provided)
SUPP (Supplementary Features)
CWRF (Body Recess Nominal Diameter)
CWSF (Nominal Radius)
CWSK (Nominal Distance From Flat To Radial Center)

INC 05464 - GEAR (1), HELICAL – App Key 'AF'

Delete the following MRCs:
CWSB (Bore Nominal Width)
CWSK (Nominal Distance From Flat To Radial Center)
CWSF (Nominal Radius)

AAJF (Thread Direction)

INC 05465 - GEAR (1), INTERNAL – App Key 'AG'

Delete the following MRCs:
TMQY (Furnished Items And Quantity)
CWCN (Nominal Width Across Flats)
CWZC (Nominal Distance From End To Second Groove)
CWXY (First Groove Nominal Width)
CWYL (Nominal Distance From End To First Groove)

INC 05466 - GEAR (1), SPUR – App Key 'AH'

Delete the following MRCs:
CWKJ (Mounting Hole Thread Tolerance Class)
CWCK (Nominal Thickness)
CRNZ (Mounting Hole Thread Pitch In Millimeters)
CWMY (Pitch Height)

INC 05467 - GEAR (1), WORM – App Key 'AJ'

Delete the following MRCs:
CWSF (Nominal Radius)
CWSB (Bore Nominal Width)
CWYR (Second Groove Nominal Width)
CWNY (Pilot Nominal Length)
CWKJ (Mounting Hole Thread Tolerance Class)
CWYN (Pilot Nominal Diameter)

INC 05468 - GEAR (1), WORM WHEEL – App Key 'AK'

Delete the following MRCs:
CWSB (Bore Nominal Width)
CWSF (Nominal Radius)

INC 05135 – GEAR RACK - App Key 'AL'

Delete the following MRCs:
TMQY (Furnished Items And Quantity)
CBBL (Features Provided)

INC 28375 - GEAR SECTOR (1), BEVEL – App Key 'AM'

Delete the following MRCs:
CWSK (Nominal Distance From Flat To Radial Center)
TMQY (Furnished Items And Quantity)
CWSF (Nominal Radius)

INC 28376 - GEAR SECTOR (1), HELICAL – App Key 'AN'

Delete the following MRCs:
CWXD (Arc Nominal Length)
STDC (Surface Treatment Document And Classification)

INC 28377 - GEAR SECTOR (1), SPUR – App Key 'AP'

Delete the following MRCs:
TMQY (Furnished Items And Quantity)
CBBL (Features Provided)
CWSF (Nominal Radius)
CWSK (Nominal Distance From Flat To Radial Center)

INC 28378 - GEAR SECTOR (1), WORM WHEEL – App Key 'AQ'

Delete the following MRCs:
CQQR (Thread Pitch In Millimeters)
CBBL (Features Provided)

INC 28187 - GEAR-SLIP CLUTCH (1), SPUR – App Key 'AR'

Delete the following MRCs:
TMQY (Furnished Items And Quantity)
STDC (Surface Treatment Document And Classification)

INC 36626 - GEAR SECTOR (1), INTERNAL – App Key 'AS'

Delete the following MRC:
BDJT (Pitch Radius)